



simpass

ENDO14

.014" Rx PTA BALLOON DILATATION CATHETER

LOW PROFILE Rx DESIGN

Best choice to reach distal vessels

IMPROVED PUSHABILITY

Enables to cross complex lesions with ease

GUIDEWIRE TRACKABILITY

Outstanding guidewire trackability with low friction inner lumen

SUPERIOR CROSSING PERFORMANCE

Balloon folding geometry minimizes profile & allows smooth rewrap

Product Code (90/ 145/ 160 cm)	Balloon Diameter (mm)	Balloon Length (mm)	Nominal / RBP (atm)	Recommended Introducer Sheath (Fr)
SPE20020-xx	2.0	20	8 / 16	4F
SPE20040-xx	2.0	40	8 / 16	4F
SPE20060-xx	2.0	60	8 / 16	4F
SPE20080-xx	2.0	80	8 / 16	4F
SPE200100-xx	2.0	100	8 / 16	4F
SPE200120-xx	2.0	120	8 / 16	4F
SPE200150-xx	2.0	150	8 / 16	4F
SPE200220-xx	2.0	220	8 / 16	4F
SPE25020-xx	2.5	20	8 / 16	4F
SPE25040-xx	2.5	40	8 / 16	4F
SPE25060-xx	2.5	60	8 / 16	4F
SPE25080-xx	2.5	80	8 / 16	4F
SPE250100-xx	2.5	100	8 / 16	4F
SPE250120-xx	2.5	120	8 / 16	4F
SPE250150-xx	2.5	150	8 / 16	4F
SPE250220-xx	2.5	220	8 / 16	4F
SPE30020-xx	3.0	20	8 / 16	4F
SPE30040-xx	3.0	40	8 / 16	4F
SPE30060-xx	3.0	60	8 / 16	4F
SPE30080-xx	3.0	80	8 / 16	4F
SPE300100-xx	3.0	100	8 / 16	4F
SPE300120-xx	3.0	120	8 / 16	4F
SPE300150-xx	3.0	150	8 / 16	4F
SPE300220-xx	3.0	220	8 / 16	4F
SPE35020-xx	3.5	20	8 / 16	4F
SPE35040-xx	3.5	40	8 / 16	4F
SPE35060-xx	3.5	60	8 / 16	4F
SPE35080-xx	3.5	80	8 / 16	4F
SPE350100-xx	3.5	100	8 / 16	4F
SPE350120-xx	3.5	120	8 / 16	4F
SPE350150-xx	3.5	150	8 / 16	4F
SPE350220-xx	3.5	220	8 / 16	4F
SPE40020-xx	4.0	20	8 / 16	4F
SPE40040-xx	4.0	40	8 / 16	4F
SPE40060-xx	4.0	60	8 / 16	4F
SPE40080-xx	4.0	80	8 / 16	4F
SPE400100-xx	4.0	100	8 / 16	4F
SPE400120-xx	4.0	120	8 / 16	4F
SPE400150-xx	4.0	150	8 / 16	4F
SPE400220-xx	4.0	220	8 / 16	4F

Product Code (90/ 145/ 160 cm)	Balloon Diameter (mm)	Balloon Length (mm)	Nominal / RBP (atm)	Recommended Introducer Sheath (Fr)
SPE45020-xx	4.5	20	8 / 16	4F
SPE45040-xx	4.5	40	8 / 16	4F
SPE45060-xx	4.5	60	8 / 16	4F
SPE45080-xx	4.5	80	8 / 16	4F
SPE450100-xx	4.5	100	8 / 16	4F
SPE450120-xx	4.5	120	8 / 16	4F
SPE450150-xx	4.5	150	8 / 16	4F
SPE450220-xx	4.5	220	8 / 16	4F
SPE50020-xx	5.0	20	8 / 14	4F
SPE50040-xx	5.0	40	8 / 14	4F
SPE50060-xx	5.0	60	8 / 14	4F
SPE50080-xx	5.0	80	8 / 14	4F
SPE500100-xx	5.0	100	8 / 14	4F
SPE500120-xx	5.0	120	8 / 14	4F
SPE60020-xx	6.0	20	8 / 14	5F
SPE60040-xx	6.0	40	8 / 14	5F
SPE60060-xx	6.0	60	8 / 14	5F
SPE60080-xx	6.0	80	8 / 14	5F
SPE70020-xx	7.0	20	8 / 14	5F
SPE70040-xx	7.0	40	8 / 14	5F
SPE70060-xx	7.0	60	8 / 14	5F
SPE70080-xx	7.0	80	8 / 14	5F

*Please advise to sales representative for different size requests.

Nominal Pressure	8 atm
Rated Burst Pressure	2mm - 4.5mm : 16 atm 5mm - 7mm : 14 atm
Markers	Swaged 1mm Platinum Iridium Markers (Distal & Proximal)
Guidewire Compatibility	0,014"
Tip Entry Profile	0,016"
Sheath Compatibility	2mm - 5mm : 4 Fr 6mm - 7mm : 5 Fr
Balloon Fold	2mm - 6mm : 3 Fold 7mm : 6 Fold
Catheter Coating	Hydrophilic Coating